INDEX TO

EXPERIMENTAL MECHANICS

Volume 28, 1988

TITLE INDEX

Analytical and Experimental Studies of the Surface Flaw — C.W. Smith, 194-200 (June).

Automated Analysis of Holointerferograms for the Determination of Surface Displacement — D.R. Matthys, T.D. Dudderar and J.A. Gilbert, 86-91 (Mar.).

Automatic Analysis of Moiré Fringe Patterns by Using an Image-Processing System — P.Ning and W. Peng, 350-354 (Dec.).

Biaxial Testing of Fiber Composites Using Tubular Specimens — S.R. Swanson, A.P. Christoforou and G.E. Colvin, Jr., 238-243 (Sept.).

Comparison of the Techniques of Transmitted Caustics and Photoelasticity as Applied to Fracture — H. Nigam and A. Shukla, 123-131 (June).

Comparison of the Techniques of Transmitted Caustics and Photoelasticity as Applied to Fracture — Discussion by P.S. Theocaris, 131-136 (June).

Crack Profiles in Mortar Measured by Holographic Interferometry — R.A. Miller, J.P. Shah and H.I. Bjelkhagen, 388-394 (Dec.).

Crack Stability in Two Brittle Nonmetallic Beam Systems — F.I. Baratta, 310-314 (Sept.).

Cracking Behavior of Brick Walls with Steel-Stud Backup, The — J.O. Arumala, 177-181 (June).

Damage Assessment Based on the Structural Frequency-Response Function — W.T. Springer, K.L. Lawrence and T.J. Lawley, 34-37 (Mar.).

Determination of Acoustic-Emission Sites Using a Digital Nondestructive-Evaluation Workstation — B.A. Barna, J.A. Johnson and R.T. Allemeier, 210-213 (June).

Development of a Modified Double-Cantilever-Beam Specimen for Measuring the Fracture Energy of Rubber to Metal Bonds, The — D.R. Lefebvre, D.A. Dillard and H.F. Brinson, 38-44 (Mar.).

Development of Viscoplastic Constitutive Equation Through Biaxial Material Testing — J.L. Ding and S.R. Lee, 304-309 (Sept.).

Double-Light-Beam Method in Three-Dimensional Scattered-Light Photoelasticity, The — X.-L. Liu, S.-C. Pan and L.-Z. Ha, 60-64 (Mar.).

Ductile and Brittle Fracture Analysis of Surface Flaws Using CTOD — T.L. Anderson, 188-193 (June).

Dynamic Measurements of Initiation Toughness at High Loading Rates — J.W. Dally and D.B. Barker, 298-303 (Sept.).

Effect of Flaws on the Strength of Si_3N_4 — J.P. Singh, 201-204 (June).

Effect of Sequence of Combined Loading on Buckling of Stiffened Shells — H. Abramovich, T. Weller and J. Singer, 1-13 (Mar.).

Elastic-Plastic *J* Analysis for an Inner Surface Flaw in a Pressure Vessel — W. Brocks and H.-D. Noack, 205-209 (June).

Evaluation of an Applied Plane-Stress Tensor Distribution Using Ultrasonic Shear Waves — M. Janssen, 226-231 (Sept.).

Exact Interpretation of Moiré Fringe Patterns in Digital Images — C.A. Lee, T.G. Richards and R.E. Rowlands, 409-416 (Dec.).

Experiment for Determining the Euler Load by Direct Computation, An — G.A. Thurston and P.A. Stein, 70-76 (Mar.).

Experimental Investigation of the Influence of Stiffened Torsional Rigidity on Buckling of Compression Panels, An — J.M. Minguez, 336-339 (Dec.).

Experimental Study of the Rock-Bit Interaction — B.S. Aadnoy, 249-253 (Sept.).

Experimental Study of Wire Strains in an Undamaged and Damaged Steel Strand Subjected to Tensile Load, An — P. Cappa, 346-349 (Dec.).

Fatigue Crack Closure of Surface Flaws Loaded in Pure Bending — S.K. Ray and A.F. Grandt, 273-280 (Sept.).

Fracture Energy for Three-Point-Bend Tests on Singled-Edge-Notched Beams — L.J. Malvar and G.E. Warren, 266-272 (Sept.).

Fracture of Composite Laminates Containing Cracks Due to Shear Loading — S. Tan and R. Kim, 364-372 (Dec.).

High-Rate Decremental-Strain-Rate Test — A. Gilat and Y.H. Pao, 322-325 (Sept.).

High-Temperature Strain-Gage Behavior on Carbon Materials — R. Steindler, 244-248 (Sept.).

Holographic Velocimetry for Flow Diagnostics — P. Schuster and J. Wagner, 402-408 (Dec.).

Image-Processing Techniques in Laser-Speckle Photography with Application to Hybrid Stress Analysis — Discussion by G.H. Kaufmann, 187 (June).

Improvement of End-Boundary Conditions for Off-Axis Tension Specimen Use, The — S.M. Cron, A.N. Palazotto and R.S. Sandhu, 14-19 (Mar.).

Influence of Grating Characteristics on Moiré Fringe Multiplication, The — S.M. Graham and R.J. Sanford, 329-335 (Dec.).

Interferometric-Fiber-Optic Strain Sensor — J.S. Sirkis and C.E. Taylor, 170-176 (June).

Interferometric Testing at Very High Temperatures by TV Holography (ESPI) — J.T. Malmo, O.J. Lokberg and G.A. Slettemoen, 315-321 (Sept.).

Interlaminar Shear Strength of Cloth-Reinforced Composites — N.J. Pagano and R.Y. Kim, 117-122 (June).

J Resistance Curves in Aluminum SEN Specimens Using Moire Interferometry — B.S.-J. Kang and A.S. Kobayashi, 154-158 (June).

Lamb Solution and Rayleigh-Wave-Induced Cracking, On the — J.F. Cardenas-Garcia and D.C. Holloway, 105-109 (June).

Laser Polarimeter for Measuring Angular Displacement of Bend Bars — J.W. Wagner, J.B. Deaton and E.M. Hackett, 45-49 (Mar.).

Magnetoelastic Buckling: Why Theory and Experiment Disagree — M.O. Peach, N.S. Christopherson, J.M. Dalrymple and G.L. Viegelahn, 65-69 (Mar.).

Measurement of Residual Stress by the Hole-Drillin Method: General Stress-Strain Relationship and Its Solution — J.-Y. Wang, 355-358 (Dec.).

Measurement of Residual Stress by the Hole-Drilling Method: On the Direction of Maximum Residual Stress — J.Y. Wang, 24-26 (Mar.).

Mechanical and Optical Characterization of Cellulose Acetate — H. Ishikawa and S. Tadano, 221-225 (Sept.).

Mode I Fracture-Energy Methods for Concrete — L.M.E. Refai and S.E. Swartz, 395-401 (Dec.).

Mode II Fracture-Parameter Estimates for Concrete from Beam Specimens — S.E. Swartz, L.W. Lu, L.D. Tang, and T.M.E. Refai, 146-153 (June).

Modified Dual-Mass Amplifier for High Strain-Rate Testing of Sifcon in Uniaxial Compression, A — J.W. Berglund, 281-287 (Sept.).

New Reusable Quadriaxial Strain Transducer, A — D. Guitard, J.L. Seichepine and A. Vautrin, 50-59 (Mar.).

New Technique for Ultrasonic-Nondestructive Evaluation of Thin Specimens, A — V.K. Kinra and V. Dayal, 288-297 (Sept.).

Optimization Process in Tall Beams — A.J. Durelli and B. Ranganayakamma, 259-265 (Sept.).

Overdeterministic Approach for Measuring K_I Using Strain Gages, An — J.R. Berger and J.W. Dally, 142-145 (June).

Photoelastic Analysis of a Thin-Walled Compressor Housing — R.O. Case and H. Mahfuz, 98-104 (Mar.).

Process Zone and Acoustic-Emission Measurements in Concrete — A. Maji and S.P. Shah, 27-33 (Mar.).

Projection-Speckle Digital-Correlation Method for Surface-Displacement Measurement — P. Sriram and A. Hanagud, 340-345 (Dec.).

Residual-Stress Distributions Produced by Strain-Gage Surface Preparation — P.S. Prevey, 92-97 (Mar.).

Residual-Stress Measurements in Time-Controlled Quenched Austenitic Stainless Steel — D. Huang, W. Mayo and Y. Chen, 359-363 (Dec.).

Simple Method for Measuring Local Buckling of Thin Plates, A — Z.T. Sang, K.C. Chang and G.C. Lee, 20-23 (Mar.).

Small Attachable Interferometric Strain Gages — W.N. Sharpe, Jr. and K.C. Wang, 136-141 (June).

Small Surface and Corner Crack Propagation in Aluminum and Steel Alloys — M. Ramulu, 214-220 (June).

Strain Analysis for Extrusion of Powder Metals — D.G. Berghaus, R.J. Primas and H.B. Peacock, 232-237 (Sept.).
Stresses in a Bonded Wafer — V.J. Parks, 77-85 (Mar.).
Study of Pure and Mixed-Mode Fracture of a Brittle Material — J. Royer, 382-387 (Dec.).
Transient Thermal Fracture of Cracked Plates — K. Kokini and M.A. Long, 373-381 (Dec.).
Ultrasonic-Image Evaluation of Microstructural Damage Accumulation in Materials — G.C. Knollman and R.C. Yee, 110-116 (June).
Use of Electrical-Resistance Foil Strain Gages for Plastic-Wave Studies in Solids, On the — A.S. Khan and C. Hsiao, 254-258 (Sept.).
Use of Iosipescu Specimens, The, Discussion — J.L. Sullivan, 326-328 (Sept.).
Variation in Stress-Intensity Factor and Back-Surface Displacement for Surface Cracks — V.M. Gensheimer and P.F. Packman, 182-187 (June).
Visualization of the Abrasive-Waterjet Cutting Process — M. Hashish, 159-169 (June).

AUTHOR INDEX

Aadnoy, B.S. — Experimental Study of the Rock-Bit Interaction, 249-253 (Sept.).
Abramovich, H. — Effect of Sequence of Combined Loading onBuckling of Stiffened Shells, 1-13 (Mar.).
Allemeier, R.T. — Determination of Acoustic-EmissionSites Using a Digital Nondestructive-Evaluation Workstation,210-213 (June).
Anderson, T.L. — Ductile and Brittle Fracture Analysis ofSurface-Flaws Using CTOD, 188-193 (June).
Arumala, J.O. — The Cracking Behavior of Brick Walls withSteel-Stud Backup, 177-181 (June).
Baratta, F.I. — Crack Stability in Two Brittle Nonmetallic Beam Systems, 310-314 (Sept.).
Barker, D.B. — Dynamic Measurements of Initiation Toughness at High Loading Rates, 298-303 (Sept.).
Barna, B.A. — Determination of Acoustic-Emission Sites Using a Digital Nondestructive-Evaluation Workstation, 210-213 (June).
Berger, J.R. — An Overdeterministic Approach for Measuring K_I Using Strain Gages, 142-145 (June).
Berghaus, D.G. — Strain Analysis for Extrusion of Powder Metals, 232-237 (Sept.).
Berglund, J.W. — A Modified Dual-Mass Amplifier for High Strain-Rate Testing of Sifcon in Uniaxial Compression, 281-287 (Sept.).
Bjelkhagen, H.I. — Crack Profiles in Mortar Measured by Holographic Interferometry, 388-401 (Dec.).
Brinson, H.F. — The Development of a Modified Double-Cantilever-Beam Specimen for Measuring the Fracture Energy of Rubber to Metal Bonds, 38-44 (Mar.).
Brocks, W. — Elastic-Plastic *J* Analysis for an Inner Surface Flaw in a Pressure Vessel, 205-209 (June).
Cappa, P. — An Experimental Study of Wire Strains in an Undamaged and Damaged Steel Strand Subjected to Tensile Load, 346-349 (Dec.).
Cardenas-Garcia, J.F. — On the Lamb Solution and Rayleigh-Wave-Induced Cracking, 105-109 (June).
Case, R.O. — Photoelastic Analysis of a Thin-Walled Compressor Housing, 98-104 (Mar.).
Chang, K.C. — A Simple Method for Measuring Local Buckling of Thin Plates, 20-23 (Mar.).
Chen, Y. — Residual-Stress Measurements in Time-Controlled Quenched Austenitic Stainless Steel, D. Huang, W. Mayo and Y. Chen 359-363 (Dec.).
Christoforou, A.P. — Biaxial Testing of Fiber Composites Using Tubular Specimens, 238-243 (Sept.).
Christopherson, N.S. — Magnetoelastic Buckling Why Theory and Experiment Disagree, 65-69 (Mar.).
Colvin, Jr., G.E. — Biaxial Testing of Fiber Composites Using Tubular Specimens, 238-243 (Sept.).
Cron, S.M. — The Improvement of End-Boundary Conditions for Off-Axis Tension Specimen Use, 14-19 (Mar.).
Dally, J.W. — An Overdeterministic Approach for Measuring K_I Using Strain Gages, 142-145 (June).
Dynamic Measurements of Initiation Toughness at High Loading Rates, 298-303 (Sept.).
Dalrymple, J.M. — Magnetoelastic Buckling: Why Theory and Experiment Disagree, 65-69 (Mar.).
Dayal, V. — A New Technique for Ultrasonic-Nondestructive Evaluation of Thin Specimens, 288-297 (Sept.).
Deaton, J.B. — Laser Polarimenter for Measuring Angular Displacement of Bend Bars, 45-49 (Mar.).
Dillard, D.A. — The Development of a Modified Double-Cantilever-Beam Specimen for Measuring the Fracture Energy of Rubber to Metal Bonds, 38-44 (Mar.).
Ding, J.L. — Development of Viscoplastic Constitutive Equation Through Biaxial Material Testing, 304-309 (Sept.).
Dudderar, T.D. — Automated Analysis of Holointerferograms for the Determination of Surface Displacement, 86-91 (Mar.).
Durelli, A.J. — Optimization Process in Tall Beams, 259-265 (Sept.).
Gensheimer, V.M. — Variation in Stress-Intensity Factor and Back-Surface Displacement for Surface Cracks, 182-187 (June).
Gilat, A. — High-Rate Decremental-Strain-Rate Test, 322-325 (Sept.).
Gilbert, J.A. — Automated Analysis of Holointerferograms for the Determination of Surface Displacement, 86-91 (Mar.).
Graham, S.M. — The Influence of Grating Characteristics on Moiré Fringe Multiplication, 329-335 (Dec.).
Grandt, A.F. — Fatigue Crack Closure of Surface Flaws Loaded in Pure Bending, 273-280 (Sept.).
Guitard, D. — A New Reusable Quadriaxial Strain Transducer, 50-59 (Mar.).
Ha, L.-Z. — The Double-Light-Beam Method in Three-Dimensional Scattered-Light Photoelasticity, 60-64 (Mar.).
Hackett, E.M. — Laser Polarimeter for Measuring Angular Displacement of Bend Bars, 45-49 (Mar.).
Hanagud, A. — Projection-Speckle Digital-Correlation Method for Surface-Displacement Measurement, 340-345 (Dec.).
Hashish, M. — Visualizaiton of the Abrasive-Waterjet Cutting Process, 159-169 (June).
Holloway, D.C. — On the Lamb Solution and Rayleigh-Wave-Induced Cracking, 105-109 (June).
Hsiao, C. — On the Use of Electrical-Resistance Foil Strain Gages for Plastic-Wave Studies in Solids, 254-258 (Sept.).
Huang, D. — Residual-Stress Measurements in Time-Controlled Quenched Austenitic Stainless Steel, 359-363 (Dec.).
Ishikawa, H. — Mechanical and Optical Charaterization of Cellulose Acetate, 221-225 (Sept.).
Janssen, M. — Evaluation of an Applied Plane-Stress Tensor Distribution Using Ultrasonic Shear Waves, 226-231 (Sept.).
Johnson, J.A. — Determination of Acoustic-Emission Sites Using a Digital Nondestructive-Evaluation Workstation, 210-213 (June).
Kang, B.S.-J. — *J* Resistance Curves in Aluminum SEN Specimens Using Moiré Interferometry, 154-158 (June).
Kaufmann, G.H. — Image-Processing Techniques in Laser-Speckle Photography with Application to Hybrid Stress Analysis, Discussion, 187 (June).
Khan, A.S. — On the Use of Electrical-Resistance Foil Strain Gages for Plastic-Wave Studies in Solids, 254-258 (Sept.).
Kim, R.Y. — Interlaminar Shear Strength of Cloth-Reinforced Composites, 117-122 (June).
Fracture of Composite Laminates Containing Cracks Due to Shear Loading, 364-372 (Dec.).
Kinra, V.K. — A New Technique for Ultrasonic-Nondestructive Evaluation of Thin Specimens, 288-297 (Sept.).
Knollman, G.C. — Ultrasonic-Image Evaluation of Microstructural Damage Accumulation in Materials, 110-116 (June).
Kobayashi, A.S. — *J* Resistance Curves in Aluminum SEN Specimens Using Moiré Interferometry, 154-158 (June).
Kokini, K. — Transient Thermal Fracture of Cracked Plates, 373-381 (Dec.).
Lawley, T.J. — Damage Assessment Based on the Structural Frequency-Response Function, 34-37 (Mar.).
Lawrence, K.L. — Damage Assessment Based on the Structural Frequency-Response Function, 34-37 (Mar.).
Lee, C.A. — Exact Interpretation of Moiré Fringe Patterns in Digital Images, 409-416 (Dec.).
Lee, G.C. — A Simple Method for Measuring Local Buckling of Thin Plates, 20-23 (Mar.).
Lee, S.R. — Development of Viscoplastic Constitutive Equation Through Biaxial Material Testing, 304-309 (Sept.).
Lefebvre, D.R. — The Development of a Modified Double-Cantilever-Beam Specimen for Measuring the Fracture Energy of Rubber to Metal Bonds, 38-44 (Mar.).
Liu, X.-L. — The Double-Light-Beam Method in Three-Dimensional Scattered-Light Photoelasticity, 60-64 (Mar.).
Lokberg, O.J. — Interferometric Testing at Very High Temperatures by TV Holography (ESPI), 315-321 (Sept.).
Long, M.A. — Transient Thermal Fracture of Cracked Plates, 373-381 (Dec.).
Lu, L.W. — Mode II Fracture-Parameter Estimates for Concrete from Beam Specimens, 146-153 (June).
Mahfuz, H. — Photoelastic Analysis of a Thin-Walled Compressor Housing, 98-104 (Mar.).
Maji, A. — Process Zone and Acoustic-Emission Measurements in Concrete, 27-33 (Mar.).
Malmo, J.T. — Interferometric Testing at Very High Temperatures by TV Holography (ESPI), 315-321 (Sept.).
Malvar, L.J. — Fracture Energy for Three-Point-Bend Tests on Singled-Edge-Notched Beams, 266-272 (Sept.).
Matthys, D.R. — Automated Analysis of Holointerferograms for the Determination of Surface Displacement, 86-91 (Mar.).

Mayo, W. — Residual-Stress Measurements in Time-Controlled Quenched Austenitic Stainless Steel, 359-363 (Dec.).

Miller, R.A. — Crack Profiles in Mortar Measured by Holographic Interferometry, 388-394 (Dec.).

Minguez, J.M. — An Experimental investigation of the Influence of Stiffened Torsional Rigidity on Buckling of Compression Panels, 336-339 (Dec.).

Nigam, H. — Comparison of the Techniques of Transmitted Caustics and Photoelasticity as Applied to Fracture, 123-131 (June).

Ning, P. — Automatic Analysis of Moiré Fringe Patterns by Using and Image-Processing System, 350-354 (Dec.).

Noack, H.-D. — Elastic-Plastic *J* Analysis for an Inner Surface Flaw in a Pressure Vessel, 205-209 (June).

Packman, P.F. — Variation in Stress-Intensity Factor and Back-Surface Displacement for Surface Cracks, 182-187 (June).

Pagano, N.J. — Interlaminar Shear Strength of Cloth-Reinforced Composites, 117-122 (June).

Palazotto, A.N. — The Improvement of End-Boundary Conditions for Off-Axis Tension Specimen Use, 14-19 (Mar.).

Pan, S.-C. — The Double-Light-Beam Method in Three-Dimensional Scattered-Light Photoelasticity, 60-64 (Mar.).

Pao, Y.H. — High-Rate Decremental-Strain-Rate Test, 322-325 (Sept.).

Parks, V.J. — Stresses in a Bonded Wafer, 77-85 (Mar.).

Peach, M.O. — Magnetoelastic Buckling Why Theory and Experiment Disagree, 65-69 (Mar.).

Peacock, H.B. — Strain Analysis for Extrusion of Powder Metals, 232-237 (Sept.).

Peng, W. — Automatic Analysis of Moiré Fringe Patterns by Using an Image-Processing System, 350-354 (Dec.).

Prevey, P.S. — Residual-Stress Distributions Produced by Strain-Gage Surface Preparation, 92-97 (Mar.).

Primas, R.J. — Strain Analysis for Extrusion of Powder Metals, 232-237 (Sept.).

Ramulu, M. — Small Surface and Corner Crack Propagation in Aluminum and Steel Alloys, 214-220 (June).

Ranganayakamma, B. — Optimization Process in Tall Beams, 259-265 (Sept.).

Ray, S.K. — Fatigue Crack Closure of Surface Flaws Loaded in Pure Bending, 273-280 (Sept.).

Refai, T.M.E. — Mode II Fracture-Parameter Estimates for Concrete from Beam Specimens, 146-153 (June).
Mode I Fracture-Energy Methods for Concrete, 395-402 (Dec.).

Richards, T.G. — Exact Interpretation of Moiré Fringe Patterns in Digital Images, 409-416 (Dec.).

Rowlands, R.E. — Exact Interpretation of Moiré Fringe Patterns in Digital Images, 409-416 (Dec.).

Royer, J. — Study of Pure and Mixed-Mode Fracture of a Brittle Material, 382-387 (Dec.).

Sandhu, R.S. — The Improvement of End-Boundary Conditions for Off-Axis Tension Specimen Use, 14-19 (Mar.).

Sanford, R.J. — The Influence of Grating Characteristics on Moiré Fringe Multiplication, 329-335 (Dec.).

Sang, Z.T. — A Simple Method for Measuring Local Buckling of Thin Plates, 20-23 (Mar.).

Schuster, P. — Holographic Velocimetry for Flow Diagnostics, 402-408 (Dec.).

Seichepine, J.L. — A New Reusable Quadriaxial Strain Transducer, 50-59 (Mar.).

Shah, J.P. — Crack Profiles in Mortar Measured by Holographic Interferometry, 388-394 (Dec.).

Shah, S.P. — Process Zone and Acoustic-Emission Measurements in Concrete, 27-33 (Mar.).

Sharpe, Jr., W.N. — Small Attachable Interferometric Strain Gages, 136-141 (June).

Shukla, A. — Comparison of the Techniques of Transmitted Caustics and Photoelasticity as Applied to Fracture, 123-131 (June).

Singer, J. — Effect of Sequence of Combined Loading on Buckling of Stiffened Shells, 1-13 (Mar.).

Singh, J.P. — Effect of Flaws on the Strength of Si_3N_4, 201-204 (June).

Sirkis, J.S. — Interferometric-Fiber-Optic Strain Sensor, 170-176 (June).

Slettemoen, G.A. — Interferometric Testing at Very High Temperatures by TV-Holography (ESPI), 315-321 (Sept.).

Smith, C.W. — Analytical and Experimental Studies of the Surface Flaw, 194-200 (June).

Springer, W.T. — Damage Assessment Based on the Structural Frequency-Response Function, 34-37 (Mar.).

Sriram, P. — Projection-Speckle Digital-Correlation Method for Surface-Displacement Measurement, 340-345 (Dec.).

Stein, P.A. — An Experiment for Determining the Euler Load by Direct Computation, 70-76 (Mar.).

Steindler, R. — High-Temperature Strain-Gage Behavior on Carbon Materials, 244-248 (Sept.).

Sullivan, J.L. — The Use of Iosipescu Specimens, Discussion, 326-328 (Sept.).

Swanson, S.R. — Biaxial Testing of Fiber Composites Using Tubular Specimens, 238-243 (Sept.).

Swartz, S.E. — Mode II Fracture-Parameter Estimates for Concrete from Beam Specimens, 146-153 (June).
Mode I Fracture-Energy Methods for Concrete, 395-401 (Dec.).

Tadano, S. — Mechanical and Optical Characterization of Cellulose Acetate, 221-225 (Sept.).

Tan, S. — Fracture of Composite Laminates Containing Cracks Due to Shear Loading, 364-372 (Dec.).

Tang, L.D. — Mode II Fracture-Parameter Estimates for Concrete from Beam Specimens, 146-153 (June).

Taylor, C.E. — Interferometric-Fiber-Optic Strain Sensor, 170-176 (June).

Theocaris, P.S. — Comparison of the Techniques of Transmitted Caustics and Photoelasticity as Applied to Fracture, Discussion, 131-135 (June).

Thurston, G.A. — An Experiment for Determining the Euler Load by Direct Computation, 70-76 (Mar.).

Vautrin, A. — A New Reusable Quadriaxial Strain Transducer, 50-59 (Mar.).

Viegelahn, G.L. — Magnetoelastic Buckling: Why Theory and Experiment Disagree, 65-69 (Mar.).

Wagner, J.W. — Laser Polarimeter for Measuring Angular Displacement of Bend Bars, 45-49 (Mar.).
Holographic Velocimetry for Flow Diagnostics, 402-408 (Dec.).

Wang, J.Y. — Measurement of Residual Stress by the Hole-Drilling Method: On the Direction of Maximum Residual Stress, 24-26 (Mar.).
Measurement of Residual Stress by the Hole-Drilling Method: General Stress-Strain Relationship and Its Solution, 355-358 (Dec.).

Wang, K.C. — Small Attachable Interferometric Strain Gages, 136-141 (June).

Warren, G.E. — Fracture Energy for Three-Point-Bend Tests on Singled-Edge-Notched Beams, 266-272 (Sept.).

Weller, T. — Effect of Sequence of Combined Loading on Buckling of Stiffened Shells, 1-13 (Mar.).

Yee, R.C. — Ultrasonic-Image Evaluation of Microstructural Damage Accumulation in Materials, 110-116 (June)

U.S. POSTAL SERVICE

STATEMENT OF OWNERSHIP, MANAGEMENT AND CIRCULATION

(Required by 39 U.S.C. 3685)

1. TITLE OF PUBLICATION	A. PUBLICATION NO.	3. DATE OF FILING
EXPERIMENTAL MECHANICS	0 0 1 4 4 8 5 1	09/26/90
2. FREQUENCY OF ISSUE: Quarterly	A. NO. OF ISSUES PUBLISHED ANNUALLY: 4	B. ANNUAL SUBSCRIPTION PRICE: $72.00

4. COMPLETE MAILING ADDRESS OF KNOWN OFFICE OF PUBLICATION (Street, City, County, State and ZIP Code) (Not printers): Society for Experimental Mechanics, Inc., 7 School St., Bethel, CT 06801

5. COMPLETE MAILING ADDRESS OF THE HEADQUARTERS OR GENERAL BUSINESS OFFICES OF THE PUBLISHER (Not printers): Same as #4

6. FULL NAMES AND COMPLETE MAILING ADDRESS OF PUBLISHER, EDITOR, AND MANAGING EDITOR (This item MUST NOT be blank)

PUBLISHER (Name and Complete Mailing Address): K.A Gallone, Society for Experimental Mechanics, Inc., 7 School St., Bethel, CT 06801

EDITOR (Name and Complete Mailing Address): Same as above.

MANAGING EDITOR (Name and Complete Mailing Address): M.E. Yergin, Society for Experimental Mechanics, Inc., 7 School St., Bethel, CT 06801

7. OWNER (If owned by a corporation, its name and address must be stated and also immediately thereunder the names and addresses of stockholders owning or holding 1 percent or more of total amount of stock. If not owned by a corporation, the names and addresses of the individual owners must be given. If owned by a partnership or other unincorporated firm, its name and address, as well as that of each individual must be given. If the publication is published by a nonprofit organization, its name and address must be stated.) (Item must be completed)

FULL NAME	COMPLETE MAILING ADDRESS
Society for Experimental Mechanics, Inc.	7 School St., Bethel, CT 06801

8. KNOWN BONDHOLDERS, MORTGAGEES, AND OTHER SECURITY HOLDERS OWNING OR HOLDING 1 PERCENT OR MORE OF TOTAL AMOUNT OF BONDS, MORTGAGES OR OTHER SECURITIES (If there are none, so state)

FULL NAME	COMPLETE MAILING ADDRESS
None.	

9. FOR COMPLETION BY NONPROFIT ORGANIZATIONS AUTHORIZED TO MAIL AT SPECIAL RATES (Section 412.3, DMM only)
The purpose, function, and nonprofit status of this organization and the exempt status for Federal income tax purposes: (Check one)

☒ (1) HAS NOT CHANGED DURING PRECEDING 12 MONTHS ☐ (2) HAS CHANGED DURING PRECEDING 12 MONTHS (If changed, publisher must submit explanation of change with this statement.)

10. EXTENT AND NATURE OF CIRCULATION	AVERAGE NO. COPIES EACH ISSUE DURING PRECEDING 12 MONTHS	ACTUAL NO. COPIES OF SINGLE ISSUE PUBLISHED NEAREST TO FILING DATE
A. TOTAL NO. COPIES (Net Press Run)	2787	2600
B. PAID CIRCULATION 1. SALES THROUGH DEALERS AND CARRIERS, STREET VENDORS AND COUNTER SALES	0	0
2. MAIL SUBSCRIPTION	2470	2332
C. TOTAL PAID CIRCULATION (Sum of 10B1 and 10B2)	2470	2332
D. FREE DISTRIBUTION BY MAIL, CARRIER OR OTHER MEANS SAMPLES, COMPLIMENTARY, AND OTHER FREE COPIES	50	50
E. TOTAL DISTRIBUTION (Sum of C and D)	2520	2382
F. COPIES NOT DISTRIBUTED 1. OFFICE USE, LEFT OVER, UNACCOUNTED, SPOILED AFTER PRINTING	267	218
2. RETURN FROM NEWS AGENTS	0	0
G. TOTAL (Sum of E, F1 and 2 - should equal net press run shown in A)	2787	2600

11. I certify that the statements made by me above are correct and complete. (Name and title of editor, publisher, business manager, or owner) K.A Gallone Publisher